Fused silica transmission grating technology enables high resolution, high efficiency gratings that are ideal for compact spectrometers



Transmission gratings from Ibsen build on leadership in fused silica transmission grating technology. The superior performance of holography, combined with wafer-based Holostepper™ processing, makes possible high resolution, high efficiency, low noise gratings at the cost level of traditional reflection gratings.

Each Ibsen grating is a holographic masterpiece - not a replica. Fused silica grating technology is equally suitable for UV, VIS and NIR wavelength regions. Ibsen's fused silica transmission grating technology is especially applicable to Raman applications due to very high efficiency over a broad bandwidth.

Spectrometer Grating


1742 I/mm for 675 – 900

FSTG-VIS 1742-357d

1742 I/mm for 675 - 900


FSTG-VIS 1742-357d

Benefits	
High diffraction efficiency combined with high dispersion	
Low polarization dependence over broad spectral range	
Unbeatable temperature and environmental tolerance	
Transmission configuration offers flexible and tolerant design	
Low stray light and low wavefront distortion	



Parameter	Specification
Materials	Fused silica and high-power, dielectric AR coating materials
Grating area	7.785 mm x 5.785 mm
Chip size	9.375 mm x 7.375 mm
Chip thickness	1.0 mm
Grating resolution	1742 l/mm
Dispersion at 750 nm	0.13 deg/nm
Angle of incidence (AOI)	44 deg
Illumination bandwidth	785 – 1100 nm
Diffraction efficiency 675-900 nm, unpolarized	>70%, all wavelengths
Coefficient of thermal expansion (CTE)	0.5 ppm/K
Maximum operating tempature	>500 degrees C
Cleaning recommendation	First contact. Available from Photonic Cleaning

Typical grating performance







1742 I/mm for 675 - 900

FSTG-VIS 1742-357d

Configuration/definitions



Drawing



Specifications are subject to change without notice.

The above grating is an example of Ibsen's capabilities. Ibsen operates as grating partner for our customers, from being an integrated part of the grating and device / instrument design phase, to the manufacturing of prototypes, to volume manufacturing of OEM gratings.

